

0513 PUFAS EURO 3000 Vlies Direkt – Blue control

Instructions for use: *PUFAS EURO 3000 Vlies Direkt* is ideally suitable for pasting non-woven wallpapers onto the wall.

Technical specifications:

| | |
|-------------|---|
| Components: | Starch ether, poly vinyl acetate powder |
| Density: | approx. 0.3-0.4g/cm ³ |
| pH-value: | approx. 8-9 |
| Solubility: | Ready for use after approx. 5 minutes |
| Usage: | approx. 200 ml/m ² |

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply-Penetrating Primer – solvent free*.

Application: Stirring vigorously, sprinkle *PUFAS EURO 3000 Vlies Direkt* into 6 l. clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. The prepared adhesive is blue coloured.

Application onto the surface: For the modern wallpapering technique – e.g. for pasting form-stable non woven wallpaper and many others – wallpaper manufacturers recommend pasting the surface. Apply the stirred *PUFAS EURO 3000 Vlies Direkt* for 1 to 2 strips of wallpaper evenly to the surface with a lambswool roll. Lay strip of wallpaper on the fresh bed of paste and press on evenly.

Application onto the wallpaper: Paste wallpaper evenly with *PUFAS EURO 3000 Vlies Direkt* and fold over. After sufficient softening, apply on impact and press on.

After dryness the adhesive is transparent.

Always observe the wallpaper manufacturer's instructions for use.

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use.

Mixing ratio:

| for | Mixing ratio | Quantity of water per 300-g packet | Coverage of a 300-g packet |
|--|--------------|------------------------------------|----------------------------|
| non woven wallpaper heavy wallpaper | 1:20 | 6 l | 25-30 m ² |

Storage: Store in a cool and dry place!

Article No.: 0513

Available size: 300 g collapsible box

Shelf life: Min. 5 years as of production date.
Date of manufacture – see print